

TARGHEE, INC.

ENVIRONMENTAL CONSULTING

February 20, 2002

Ms. Wendy Liu
California Regional Water Quality Control Board,
Los Angeles Region
320 West 4th Street, Suite 200
Los Angeles, California 90013

Re: Groundwater Investigation and
Quarterly Monitoring Report
Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293
SLIC No. 997

2002 FEB 21 P 3:37

Dear Ms. Liu:

Targhee, Incorporated is pleased to provide you with the attached Groundwater Investigation and Quarterly Monitoring Report for the above-referenced property.

Please contact the undersigned if you have any questions or comments regarding the enclosed report.

Sincerely,

Debra Bechtold
Project Manager
Registered Environmental Assessor II
No. 20172



Paul N. McCarter
Registered Geologist #5243
Certified Hydrogeologist #HG 543

cc: Mr. Barry Moeschel
Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293

GROUNDWATER INVESTIGATION AND
QUARTERLY MONITORING REPORT

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293
SLIC No. 997

February 20, 2002


Submitted by:

Targhee, Incorporated
110 Pine Avenue, Suite 925
Long Beach, California 90802
(562) 435-8080

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.	1
SITE INFORMATION.	1
BACKGROUND.	1
SITE HEALTH AND SAFETY PLAN	2
REGISTERED PERSONNEL.	2
HYDROGEOLOGY	2
SCOPE OF WORK	2
Drilling and Sampling	2
Monitoring Well Construction.	3
Well Development.	3
Well Surveying.	3
Groundwater Sampling.	4
ANALYTICAL RESULTS.	4
Soil Analytical Data.	4
Groundwater Analytical Data	5
DISPOSAL OF NON-HAZARDOUS WASTE	6
DISCUSSION OF RESULTS	7

Local Area MapAttachment A
Facility MapAttachment B
Safety Meeting DocumentationAttachment C
Groundwater Monitoring Well Installation Report.Attachment D
Permits.Attachment E
Survey Data.Attachment F
Soils Laboratory Analysis.Attachment G
Well Sampling Data Logs.Attachment H
Groundwater Laboratory Analysis.Attachment I
Isoconcentration MapAttachment J
Non-Hazardous Waste Manifests.Attachment K



TARGHEE, INC.

ENVIRONMENTAL CONSULTING

GROUNDWATER INVESTIGATION AND
QUARTERLY MONITORING REPORT
Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293

INTRODUCTION

This report details Targhee, Incorporated's activities, findings, and conclusions with respect to Del Rey Cleaners located at 310 Culver Boulevard, Playa Del Rey, California 90293 (Attachment A). The California Regional Water Quality Control Board ("CRWQCB") requested a groundwater investigation to define the extent of groundwater contamination at the subject property.

The following activities were conducted pursuant to Targhee's Groundwater Investigation Workplan, dated October 31, 2001, for the subject site and in accordance with CRWQCB correspondence dated November 6, 2001.

This report has been prepared using the CRWQCB "General Requirements for Subsurface Investigations (Well Investigation Program)" and "Requirements for Groundwater Investigation (Well Investigation Program)".

SITE INFORMATION

The responsible party and property owner for the site is Mr. Barry Moeschel, 310 Culver Boulevard, Lomita, California 90293, phone number (310)823-0206. The subject site is an existing dry cleaners. The dry cleaning equipment at the facility is a self-contained unit which has been in use since about 1984. Prior to 1984, other methods of dry cleaning were utilized.

BACKGROUND

The subject property has operated as a dry cleaners for approximately 30 years. Results of previous soil investigations have been documented in reports prepared by other consultants and previously submitted to the CRWQCB. The soil sample results identified concentrations of Perchloroethene ("PCE") ranging up to 2,300 micrograms per kilogram (ug/kg, or parts per billion) at five feet below ground surface ("bgs"). Groundwater was reported by this consultant to be at approximately ten feet bgs.

Groundwater Investigation and
Quarterly Monitoring Report
310 Culver Boulevard
Playa Del Rey, CA 90293
February 20, 2002
Page 2

A facility map is provided as Attachment B. This map depicts the equipment location and includes a north arrow, property lines, and adjacent streets. Dates of completion of buildings or pavings are unknown.

SITE HEALTH AND SAFETY PLAN

A site-specific Health and Safety Plan, commensurate with the scope and nature of work was prepared and was provided as Attachment C to Targhee's October 2001 Workplan. A meeting was held with all field personnel prior to initiation of field work. Documentation of the meeting is provided as Attachment C of this report.

REGISTERED PERSONNEL

Mr. Paul McCarter of Targhee, a California Registered Geologist and Certified Hydrogeologist, was on site to direct the investigation and personally supervised and/or actually conducted the work associated with this project. The report contains a wet ink signature by the registered geologist.

HYDROGEOLOGY

The hydrogeology of the site and vicinity was determined from available published literature, regulatory agency data, and observations made during the well installation operations. The geologist's report provided in Attachment D describes the hydrology of the site and vicinity.

SCOPE OF WORK

On January 8, 2002, three groundwater monitoring wells were completed at the subject site. The October 2001 workplan describes the construction of the three onsite monitoring wells. The locations of the groundwater monitoring wells are depicted on Attachment B.

Prior to the initiation of this workplan, permits were obtained from the Los Angeles County Department of Health Services and the Los Angeles County Department of Public Works. Copies of the permits are provided as Attachment E.

The drilling, sampling, well installation and development were performed under the direct supervision and/or were personally supervised by Mr. Paul McCarter of Targhee. A complete description of the soil boring and well construction procedures is provided as the geologist's report which is contained in Attachment E.

Drilling and Sampling

The drilling was completed using a hollow-stem auger drill rig. Undisturbed soil samples were collected from each boring beginning at a depth of 5 feet below ground surface ("bgs") and continuing to the final completed depth of the boring for logging purposes. The boring logs are complete and legible and include a description of earth materials, conditions, and classifications per the Unified Soil Classification System ("USCS"); lithographic column with USCS abbreviations and symbols; sample depth in feet; blow counts and percentage of sample recovered; and, vapor readings of samples using a photoionization detector. A complete description of the drilling and sampling procedures is provided in the geologist's report contained in Attachment D.

Monitoring Well Construction

Following soil sampling procedures, each of the soil borings was converted to a groundwater monitoring well. The geologist's report provided in Attachment D describes the monitoring well construction.

Well Development

Prior to initiating well development, each well was gauged to determine the static water level. Following gauging, each of the wells was subjected to development procedures consisting of a combination of surging and pumping. Good recharge was observed in the wells.

All development equipment was steamed cleaned and rinsed between wells. The well development waste water was disposed in accordance with regulatory requirements.

Well Surveying

On January 29, 2002, each of the wells was surveyed to a common datum plane by a licensed surveyor, Psomas of Los Angeles. A copy of the survey is provided as Attachment F.

Groundwater Sampling

Groundwater sampling occurred on January 15, 2002. Prior to purging and sampling, the monitoring wells were measured to determine the water levels. Water-level measurements were completed in each of the wells using a Keck Interface Probe. No free product was present in any of the wells. The water levels were used to determine the volume of water present in the wells as well as the direction and gradient of the groundwater flow at the site.

Following the completion of water level measurements and prior to the collection of groundwater samples, approximately 55 gallons of water were purged from each of the wells using a submersible pump. The temperature, pH, conductivity, and turbidity were obtained by Targhee after the removal of each well volume. Each of the testing instruments (Hanna Temperature-Conductivity-pH Tester and LaMotte Model 2008 Turbidity Meter) were calibrated prior to use. The measurements of these parameters are shown on the Well Sampling Data Logs contained in Attachment H. Measurements were within 10% of each other following the removal of five well volumes in each of the wells.

Groundwater samples were collected from each well using a clean PVC disposable bailer. A new bailer was used for each well. The sample was transferred from the bailer to laboratory supplied containers and stored in an iced cooler at 4°C for transportation to a State-certified laboratory.

Standard Chain-of-Custody procedures were maintained on all samples. The Chain-of-Custody Record with a request-for-analysis was initiated in the field by Targhee. Each time responsibility for custody of the samples changed, the receiving and relinquishing custodians signed the record and entered the date and time of transfer of the samples. The laboratory signed for the receipt of the samples and returned a copy of the Chain-of-Custody Record to Targhee.

ANALYTICAL RESULTS

Soil and groundwater samples were analyzed by American Scientific Laboratories, California DHS ELAP #2200.

Soil Analytical Data

All of the soil samples were prepared for analysis and were analyzed using EPA Method 8260B for Volatile Organic Compounds

("VOCs"). The positive results, in parts per billion (" $\mu\text{g}/\text{mg}$ ") are presented in the following table. The laboratory report for the soil sampling analyses are included as Attachment G.

Soil Sample Results in ppb

Sample No.	PCE	DCE	Benzene	Ethyl-benzene	Xylenes	Naphthalene	Toluene
MW1-5.5'	ND	18	ND	7	ND	ND	ND
MW2-6.5'	3,590	ND	ND	ND	ND	ND	ND
MW2-10.5'	3,110	ND	ND	ND	ND	ND	ND
MW3-6.5'	ND	ND	ND	ND	ND	ND	ND
MW3-10.5'	ND	ND	16	5	7	130	4
MW3-15.5'	ND	ND	ND	ND	ND	ND	ND

ND - None Detected

Sample MW3-10.5 also contained acetone at 71 $\mu\text{g}/\text{kg}$, sec-butylbenzene at 45 $\mu\text{g}/\text{kg}$, isopropylbenzene at 79 $\mu\text{g}/\text{kg}$, and n-propylbenzene at 128 $\mu\text{g}/\text{kg}$.

Groundwater Analytical Data

Each groundwater sample was analyzed for VOCs using EPA Method 8260B. The groundwater samples were also analyzed for sulfate, nitrate, ferrous iron, dissolved oxygen, Redox potential, and methane. The analytical results for VOCs are presented in the following table. The laboratory report for the groundwater sampling event is provided as Attachment I. An isoconcentration contour map of PCE is included as Attachment J.

January 15, 2002 Results
($\mu\text{g}/\text{L}$)

Sample No.	PCE	TCE	MCL
MW1	2,440	134	5
MW2	160	ND	5
MW3	43,500	ND	5

TCE - Trichloroethene

MCL - Maximum Contaminant Level

ND - None Detected

The groundwater monitoring wells were also sampled and analyzed for General Minerals Content. The results are presented below.

<u>Analyte</u>	<u>Sample No.</u>	<u>MW1</u>	<u>MW2</u>	<u>MW3</u>
Alkalinity, Total	190	100	170	170
Bicarbonate	130	100	170	170
Carbonate	ND	ND	ND	ND
Hydroxide	ND	ND	ND	ND
Chloride	108	99.2	83.6	83.6
Conductivity	944	953	838	838
Fluoride	10.8	2.54	9.77	9.77
Hardness	179	57.4	149	149
Nitrate	9.78	11.4	9.84	9.84
pH	7.60	7.56	7.72	7.72
Sulfate	110	142	103	103
Surfactants	0.08	0.08	0.30	0.30
Total Dissolved Solids	572	574	501	501
Calcium	34.8	7.44	25.9	25.9
Copper	ND	ND	ND	ND
Iron	1.05	0.13	1.55	1.55
Magnesium	22.4	9.42	20.4	20.4
Manganese	0.023	0.017	0.039	0.039
Potassium	6.8	7.81	6.82	6.82
Sodium	117	156	114	114
Zinc	ND	ND	ND	ND

Barely
~ Brackish CL level
(> 500 mg/L)

DISPOSAL OF NON-HAZARDOUS WASTE

During the course of this investigation, soil cuttings and purged groundwater were removed from the site on a daily basis. The drummed waste was handled by Prime Environmental Services of El Monte, California. The non-hazardous waste manifests are included as Attachment K.

DISCUSSION OF RESULTS

Targhee conducted a groundwater investigation at Del Rey Cleaners, 310 Culver Boulevard, Playa Del Rey, California to determine the impact to groundwater from the use of PCE at the facility. The investigation consisted of installation of three groundwater monitoring wells and groundwater sampling. The monitoring results indicate that the depth to water ranges from

Groundwater Investigation and
Quarterly Monitoring Report
310 Culver Boulevard
Playa Del Rey, CA 90293
February 20, 2002
Page 7

about 4 to 13 feet bgs from north to south across the property and that the groundwater gradient is directed to the southeast.

As depicted on the Site Plot Plan, the monitoring wells were located to the north, south, and west of the facility. Monitoring well MW2 is located in close proximity to the equipment and former

PCE storage area inside the building. Soil samples collected at 6.5 and 10.5 feet bgs at boring MW2 contained concentrations of PCE of 3,590 and 3,110 ug/kg, respectively.

PCE was not encountered in the soil samples collected from monitoring wells MW1 and MW3.


Minor concentrations of aromatic petroleum hydrocarbons were identified in several of the soil samples. Aromatic hydrocarbons at these low concentrations do not pose an impact to human health or the environment. However, the presence of the aromatic hydrocarbons is an indication of historic uses that have not been clearly defined at this time.

The groundwater analytical results identified elevated concentrations of PCE at monitoring well MW1, ^{down}upgradient of the possible source area. The concentrations of PCE encountered in wells MW2 and MW3 are significant and represent a major impact to groundwater. However, the highest concentration was identified at monitoring well MW3 which is cross-gradient to well MW2. Based on the gradient and PCE concentrations the source area(s) cannot be fully determined at this time.

The General Minerals analyses indicates that there is very little, if any, influence on the groundwater due to the sites proximity to the coast.


The next groundwater monitoring event is scheduled for late March 2002.

ATTACHMENT A







● SITE: 310 Culver Boulevard, Playa Del Rey, CA, 90293, Page & Grid 702 A3

ATTACHMENT B



SYMBOLS

-  B4 Previous soil boring
-  Drum storage area
-  MW1 Groundwater monitoring well



TARGHEE, INC.
ENVIRONMENTAL CONSULTING

110 Pine Avenue, Suite 925
Long Beach, CA 90802
(562) 435-8080

FACILITY MAP

DEL RAY CLEANERS
310 CULVER BOULEVARD
PLAYA DEL RAY, CALIFORNIA 90293

ATTACHMENT B

FEBRUARY 20, 2002

ATTACHMENT C

1-8-2002

Print

Sign

Debra Bickford

Debra Bickford

SESSA COSTA



Ismael Leonos

Ismael Leonos

Refugio Zavala

Refugio Zavala

Paul McCarter

P. McCarter

ATTACHMENT D

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293

February 20, 2002



Paul N. McCarter
Registered Geologist #5243
Certified Hydrogeologist #HG 543


Submitted by:

Targhee, Incorporated
110 Pine Avenue, Suite 925
Long Beach, California 90802
(562) 435-8080

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
METHODOLOGY.	1
Soil Sampling Methodology	1
Well Installation Methodology	3
HYDROGEOLOGY	4
Regional Hydrogeology	4
Site Hydrogeology	5

WELL LOGS.ATTACHMENT A
GROUNDWATER CONDITIONSATTACHMENT B



TARGHEE, INC.

ENVIRONMENTAL CONSULTING

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, California 90293

INTRODUCTION

On January 8, 2002, Targhee, Incorporated performed a groundwater monitoring well installation program at the Del Rey Cleaners property at 310 Culver Boulevard in Playa Del Rey, California. The program consisted of the installation of three off-site monitoring wells (MW1, MW2, and MW3) at the site.

The installation of the wells was performed by Gregg Drilling and Testing of Signal Hill, California. The procedures were performed under the supervision of a California Registered Geologist/Certified Hydrogeologist. Well construction details are contained on the well logs in Attachment A.

METHODOLOGY

Wells MW1, MW2, and MW3 were installed on the site as 2-inch diameter wells. Well MW1 was located in the parking lot north of the building, well MW2 was located in the planter south of the building, and well MW3 was located in the parking lot west of the building. The locations of the wells are shown on Attachment B.

Each of the wells was completed using a Marl M5T limited-access drill rig. The methodology involved with obtaining soil samples from the initial borings and the installation of the wells is contained in the following sections.

Soil Sampling Methodology

Each of the wells was initially drilled as a soil boring using a Marl M5T limited-access hollow-stem auger drill rig equipped with 6-inch outside-diameter augers. Soil samples were obtained at 5-foot depth intervals throughout the initial well borings until heaving sands in groundwater prevented the collection of viable samples.

Soil samples were obtained at interval lengths of 1.5 feet through the hollow-stem augers using a modified California split-spoon sampler. The split-spoon sampler was advanced into the ground using a hydraulic hammer. Samples were numbered with

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 2

respect to the boring number and the sample depth. The bottom of the sample interval in each case corresponded to the depth portion of the sample number. For example, sample MW2-10.5 was collected from a depth of 10.5 feet bgs in the initial boring of MW2.

Following collection of the samples from each of the initial borings, the brass sampling rings were removed from the sampler. The lowermost of the brass sampling rings was retained for sampling purposes. Soil samples designated for analysis for volatile organic compounds ("VOCs") were obtained using the sampling methodology detailed in SW-846 Method 5035. A 5-gram sample was collected and placed in a pre-weighed, labeled 40 ml VOA vial with a septum sealed screw cap. The vial, which contained a stirring bar and a sodium bisulfate preservative solution, was sealed immediately upon the soil being placed into it. The vials were immediately stored in an iced cooler at 4°C prior to transport within 24 hours to a laboratory certified by the California Department of Health Services.

Standard Chain-of-Custody procedures were maintained on all samples. The Chain-of-Custody Record with a request for analysis was initiated in the field by Targhee, Incorporated. Each time responsibility for custody of the samples changed, the receiving and relinquishing custodians signed the record and entered the date and time of transfer of the samples. The laboratory signed for the receipt of the samples and returned a copy of the Chain-of-Custody Record to Targhee.

A portion of each soil interval was used for soil classification purposes and for field estimation of VOCs using a MiniRAE Plus Photoionization Detector ("PID"). The PID, which contains a 10.6 eV lamp, was calibrated prior to field use. To perform this field test, approximately one cubic inch of soil was taken from the remaining brass rings and placed into an air-tight plastic bag for approximately five minutes. The bag was subsequently perforated, the tip of the PID was inserted into the perforation, and the value of the VOCs in parts per million ("ppm") was read directly from the instrument. It should be noted, however, that this field screening technique is a qualitative measurement only, and it is not a substitute for laboratory analyses.

All samples were collected by a California Registered Geologist/Certified Hydrogeologist who entered the information concerning the soil sampling intervals, PID readings, and soil lithology onto the well logs. Well logs are contained in Attachment A.

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 3

Well Installation Methodology

Following the completion of the drilling and sampling procedures, each of the initial borings was converted into a 2-inch diameter groundwater monitoring well. Each of the borings was overdrilled using 8-inch outside-diameter hollow-stem augers.

Wells MW1 and MW3 were initially drilled to a total depth of 30.5 feet below ground surface (bgs), and the wells were set at a total depth of 30 feet bgs. Well MW2 was initially advanced to a depth of 35.5 feet bgs; however, the lithology in this well indicated that a clay layer was present between 30 and about 33 feet bgs. As a result, the portion of the boring between 30 and 35.5 feet bgs in well MW2 was backfilled with bentonite through the 6-inch diameter augers concurrent with their removal from the boring. Well MW2 was ultimately set at a depth of 29.5 feet bgs.

Due to the topographic variation of the surface of the site and the levels at which groundwater was encountered in the initial borings, wells MW1 and MW3 were screened between a depth of 5 and 30 feet bgs. Groundwater was initially encountered at a depth of 7 feet bgs in MW1 and 19 feet bgs in MW3. Prior to overdrilling of well MW3, however, it was noted that the water level had risen above a partially confining clay layer to a level of about 8 feet bgs, and it was determined that the top of the screened interval should be placed at a depth of 5 feet bgs. The water level in well MW2 was encountered at a depth of 14 feet bgs, and the top of the screened interval in this well was set at 9.5 feet bgs. Well MW2 is located at an elevation of about 9 feet higher than well MW1.

Upon completion of the well drilling procedures, 2-inch, Schedule 40, slotted PVC casing (0.02" slot size) was placed inside the augers within the lower portion of the wells, and the upper portion of the wells was completed with 2-inch Schedule 40, blank PVC casing.

Clean, kiln-dried No. 2/12 sand was used as a filter pack and was placed in the annular space between the augers and the casing as the augers were sequentially removed from the boring. The sand was placed to a depth of approximately one to two feet above the top of the slotted casing. Hydrated bentonite chips (Enviroplug Medium) were placed in the annular space above the filter pack to a depth of about 1.5 feet bgs. A concrete surface seal with a flush-mounted well box was placed in the upper portion of the well above the bentonite. The materials schedule for each of the wells in feet bgs is as follows:

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 4

MATERIALS	MW1	MW2	MW3
Slotted Casing	5 - 30	9.5 - 29.5	5 - 30
Blank Casing	0 - 5	0 - 9.5	0 - 5
Filter Pack	4 - 30	7.5 - 29.5	4 - 30
Bentonite Seal	1.5 - 4	1.5 - 7.5	1.5 - 4
Surface Completion	0 - 1.5	0 - 1.5	0 - 1.5

HYDROGEOLOGY

The hydrogeology of the site and vicinity was determined from available published literature, regulatory agency data, and observations made during the well installation operations.

Regional Hydrogeology

The regional geology of the vicinity of the site is contained in the following publications:

- o California Department of Water Resources, 1961 (Reprinted 1990): Planned Utilization of the Ground Water Basins of the Coastal Plain of Los Angeles County, Appendix A Ground Water Geology, Bulletin No. 104.
- o Poland, J.F., Garrett, A.A., and Sinnott, Allen, 1959: Geology, Hydrology, and Chemical Character of Groundwaters in the Torrance-Santa Monica Area, California, U.S. Geological Survey Water-Supply Paper 1461, 425 p.
- o U.S. Geological Survey, 1964 (Photorevised 1981): Venice, California 7½ Minute Topographic Quadrangle, 1:24,000.

According to the above-referenced publications, the site is located in the southwestern corner of the Ballona Gap along the margin of the El Segundo Sand Hills. Based on information contained on the "Venice, California 7½ Minute Topographic Quadrangle", which was published by the U.S. Geological Survey in 1964 and photorevised in 1981, the site is at an approximate elevation ranging from less than 5 feet above mean sea level ("msl") in the north to more than 15 feet above msl in the south.

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 5

The land surface at the site slopes to the north at a gradient of about 250 feet/mile.

The site is underlain by Older Dune Sand deposits of Upper Pleistocene age which directly overlie gravels, sands, silts, and clays of the San Pedro Formation of Lower Pleistocene age. Alluvial deposits of Recent age may be present along the northern margin of the site. The site is located in an area where the Ballona Aquifer, which is located in the Recent-aged alluvial sediments, and the underlying Silverado Aquifer, which is located in the San Pedro Formation, become merged and are close to the land surface. The groundwater in this aquifer has been subjected to salt-water intrusion.

Groundwater data for the general area were obtained from the County of Los Angeles Department of Public Works. Well #1243B, which is located approximately 1,500 feet northwest of the site, encountered groundwater at a depth of 11.7 feet bgs which is equivalent to an elevation of 1.4 feet above msl during the gauging event on April 27, 1999.

Site Hydrogeology

The soils in the upper 35 feet of the subsurface at the site can be subdivided into three general units which appear to be dipping toward the east. These units appear to be gradational with each other and are described as follows:

- o Silty Sand and Sand

This unit directly underlies the parking lot and consists partly of reworked natural fill materials within the uppermost 3 feet. It is thickest in MW2 which is located at a higher elevation than the other two wells. It is about 8 feet thick in MW1 which is the well at the lowest elevation. This unit is characterized by a yellowish brown fine- to medium-grained silty sand and sand. A clay lens was noted in this unit between 4 and 5 feet bgs in MW1.

- o Clay and Clayey Sand

This unit is approximately 8 to 12 feet in thickness and directly underlies the Silty Sand and Sand Unit. It is grayish brown to dark gray in color and has been impacted by hydrocarbons in MW1 and MW3. The sand content of this

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 6

unit increases toward the south. This unit is saturated in MW1 and MW2; however, it appears to act as a partial confining layer in MW3.

o Sand

This unit underlies the Clay and Clayey Sand unit and extends to the bottom of each of the wells. It consists of a yellowish brown, fine- to coarse-grained sand. It is gray in color where it has been impacted by hydrocarbons in MW1. This unit is saturated in all of the wells. A partly confining clayey silt lens was noted in MW2 at 30 feet bgs; however, this lens is less than 5 feet thick and is not continuous.

PID readings obtained from the soil samples indicated the presence of hydrocarbons in the soil. Readings as high as 37 ppm were noted in the soils which were visibly impacted by hydrocarbons.

Groundwater was encountered within the Clay and Clayey Sand Unit and the underlying Sand Unit. The Clay and Clayey Sand Unit is saturated in MW1 and MW2. This unit is dryer in MW3 and appears to act as a partially confining layer to the underlying groundwater as evidenced by the upward directed head of the water table once this well was installed. The Clay and Clayey Sand Unit does not appear to be an effective barrier to groundwater movement across the site, however, and is clearly the host to the groundwater in MW1 and MW2. The lowermost portion of the upper Silty Sand and Sand Unit in MW1 and MW2 is within the groundwater zone.

Groundwater elevations were measured in monitoring wells MW1, MW2, and MW3 on January 14, 2002, and the groundwater parameters of the wells are as follows:

<u>Well No.</u>	<u>Surface Elevation</u> <u>(feet above msl)</u>	<u>Water Depth</u> <u>(feet bgs)</u>	<u>Water Elevation</u> <u>(feet above msl)</u>
MW1	8.40	3.990	4.410
MW2	16.99	12.955	4.035
MW3	11.64	7.300	4.340

GROUNDWATER WELL INSTALLATION REPORT

Del Rey Cleaners

310 Culver Boulevard

Playa Del Rey, California 90293

February 20, 2002

Page 7

The groundwater conditions beneath the site were calculated on the basis of the above groundwater parameters and are shown on the map contained in Attachment B. On January 14, 2002, groundwater at the site was flowing S 50° E at a gradient of 0.005 feet/foot or about 26 feet/mile. This direction of groundwater flow is toward the hillside and may represent regional flow conditions or possible tidal influence.

ATTACHMENT A - WELL LOGS



TARGHEE, INC.

ENVIRONMENTAL CONSULTING

110 Pine Avenue, Suite 925
Long Beach, CA 90802
(562) 435-8080

PROJECT:

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, CA 90293

LOGGER: Paul McCarter

DRILLER: Jesse Costa

PAGE 1

**WELL
NUMBER:**

MW1

DATE: January 8, 2002

DRILLING COMPANY:

Gregg Drilling & Testing, Inc.
Signal Hill, California 90806

DRILL: Marl M5T Limited Access

WELL LOCATION:

North of building in parking lot.

SAMPLING METHOD:

1.5" X 18" California Modified
Split Spoon Sampler

ELEVATION:

TOC = 8.40 msl

BORING DEPTH: 30.5

WELL DEPTH: 30'

DEPTH (feet)	SOIL/LITHOLOGY LOG		SAMPLE DATA					AIR	WELL DATA
		U.S.C.S. UNIT GRAPHIC	SAMPLE NUMBER	INTERVAL	BLOW COUNT	PID READING (ppm)	% RECOVERY	PID READING (ppm)	
0	CONCRETE: 6". SAND WITH SILT: dark yellowish brown (10YR, 4/4), probably fill, fine- to medium-grained, up to 10% fines, slightly moist.	SP SM	MW1-6.5						Flush-mounted well cover with concrete surface seal
5	SANDY CLAY: yellowish brown (10YR, 5/4), natural, up to 30% fine- to medium-grained sand, somewhat plastic, slightly moist. SILTY SAND: brown (10YR, 4/3) changing to very dark gray (2.5Y, N3/) @ 6.5 feet, fine- to medium-grained, moderate hydrocarbon odor at color change, medium-dense, slightly moist. CLAY: gray (2.5Y, N5/), plastic, moderate gasoline/ hydrocarbon odor, soft, wet (saturated), water @ 7'.	CL SM CL			NA	0	100		Concrete 2" Schedule 40 PVC blank casing Bentonite Enviroplug Medium
10		CL ML			NA	22	100		
15	SILTY CLAY: dark gray (2.5Y, N4/), somewhat plastic, moderate gasoline/fetid odor, soft, wet.	CL ML			NA	12	100		2" Schedule 40 PVC slotted casing (0.02")
20	CLAYEY SILT: very dark gray (2.5Y, N3/), moderate hydrocarbon/fetid odor, very soft, wet.	ML CL			NA	7	100		Monterey #2/12 sand filter pack
	SAND WITH SILT: dark gray (2.5Y, N4/), fine- to medium-grained, up to 10% fines, moderate hydrocarbon/fetid odor, medium-dense, wet. medium-dense, wet.	SP SM			NA	10	100		



TARGHEE, INC.

ENVIRONMENTAL CONSULTING

110 Pine Avenue, Suite 925
Long Beach, CA 90802
(562) 435-8080

PROJECT:

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, CA 90293

LOGGER: Paul McCarter

DRILLER: Jesse Costa

PAGE 1

**WELL
NUMBER:**

MW2

DATE: January 8, 2002

DRILLING COMPANY:

Gregg Drilling & Testing, Inc.
Signal Hill, California 90806

DRILL: Marl M5T Limited Access

WELL LOCATION:

South of building in planter.

SAMPLING METHOD:

1.5" X 18" California Modified
Split Spoon Sampler

ELEVATION:

TOC = 16.99 msl

BORING DEPTH: 36.5

WELL DEPTH: 29.5'

DEPTH (feet)	SOIL/LITHOLOGY LOG		SAMPLE DATA					AIR	WELL DATA
	U.S.C.S. UNIT	GRAPHIC	SAMPLE NUMBER	INTERVAL	BLOW COUNT	PID READING (ppm)	% RECOVERY	PID READING (ppm)	
0									Flush-mounted well cover with concrete surface seal
	SILTY SAND: dark yellowish brown (10YR, 4/4), fine- to medium-grained, up to 15% fines, possibly fill, slightly moist.								Concrete
5	brown (10YR, 4/3), possibly natural. dark yellowish brown (10YR, 4/4), medium-grained, loose to medium-dense, very moist.		MW2-6.5		NA	8	85		2" Schedule 40 PVC blank casing
10	up to 20% fines, loose to medium-dense, very moist.		MW2-10.5		NA	3	75		Bentonite Enviroplug Medium
15	water @ 14'. very little recovery, brown (10YR, 4/3), loose, wet.				NA	NA	<1		2" Schedule 40 PVC slotted casing (0.02")
20	SAND WITH SILT: dark gray (2.5Y, N4/), fine- to medium-grained, up to 10% fines, roots, medium-dense, wet.				NA	2	80		Monterey #2/12 sand filter pack
	CLAYEY SAND: grayish brown (2.5Y, 5/2), fine- to medium-grained, up to 40% fines (mostly clay), medium-dense, wet.				NA	2	30		

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, CA 90293

MW-2

DEPTH (feet)	SOIL/LITHOLOGY LOG		SAMPLE DATA				AIR	WELL DATA
		U.S.C.S. UNIT GRAPHIC	SAMPLE NUMBER	INTERVAL	BLOW COUNT	PID READING (ppm)	% RECOVERY	PID READING (ppm)
25								
	SAND: light olive brown (2.5Y, 5/3), medium- to coarse-grained, up to 5% fines, medium-dense, wet.	SP						
30	CLAYEY SILT: light olive brown (2.5Y, 5/4), micaceous, up to 5% very fine-grained sand, very stiff, slightly moist.	ML CL						
	SAND: pale yellow (2.5Y, 7/3), fine- to coarse-grained, medium-dense, wet.	SW						
35					NA	0	50	
40								
45								
50								
55								

Monterey #2/12 sand filter pack

2" Schedule 40 PVC slotted casing (0.02")

End cap

Bentonite Enviroplug Medium



TARGHEE, INC.

ENVIRONMENTAL CONSULTING

110 Pine Avenue, Suite 925
Long Beach, CA 90802
(562) 435-8080

PROJECT:

Del Rey Cleaners
310 Culver Boulevard
Playa Del Rey, CA 90293

PAGE 1

WELL NUMBER:

MW3

LOGGER: Paul McCarter

DRILLER: Jesse Costa

DATE: January 8, 2002

DRILLING COMPANY:

Gregg Drilling & Testing, Inc.
Signal Hill, California 90806

WELL LOCATION:

West of building in parking lot.

DRILL: Marl M5T Limited Access

SAMPLING METHOD:





1.5" X 18" California Modified
Split Spoon Sampler

ELEVATION:

TOC = 11.64 msl

BORING DEPTH: 30.5

WELL DEPTH: 30'

DEPTH (feet)	SOIL/LITHOLOGY LOG		SAMPLE DATA				AIR	WELL DATA			
			U.S.C.S. UNIT	GRAPHIC	SAMPLE NUMBER	INTERVAL	BLOW COUNT	PID READING (ppm)	% RECOVERY	PID READING (ppm)	
0	ASPHALT: 3". SILTY SAND: yellowish brown (10YR, 5/4), fine- to medium-grained, up to 20% fines, glass fragment @ 3', fill, very slightly moist.		SM								Flush-mounted well cover with concrete surface seal
5	dark yellowish brown (10YR, 4/4), up to 15% fines, natural (?), medium-dense, slightly moist to moist.				MW3-6.5		NA	0	75		Concrete
10	brown (2.5, 3/2), up to 25% fines, slight hydrocarbon odor, medium-dense, moist to very moist. CLAY: very dark gray (2.5Y, N3/), trace very fine-grained sand, micaceous, moderated hydrocarbon odor, medium-stiff, moist.		CL				NA	2 37	80		2" Schedule 40 PVC blank casing
15	CLAYEY SAND: dark gray (2.5Y, N3/), fine- to medium-grained up to 30% fines, moderate hydrocarbon/fetid odor, medium-dense, very moist, but not saturated.		SC				NA	2	90		Bentonite Enviroplug Medium
20	SAND: very little recovery, sand remnant in sampler, fine- medium-grained, water @ 19', wet.		SP								2" Schedule 40 PVC slotted casing (0.02")
	no recovery, heaving sands, wet.										Monterey #2/12 sand filter pack

DEPTH (feet)	SOIL/LITHOLOGY LOG		SAMPLE DATA				AIR	WELL DATA
		U.S.C.S. UNIT GRAPHIC	SAMPLE NUMBER	INTERVAL	BLOW COUNT	PID READING (ppm)	% RECOVERY	PID READING (ppm)
25								
30	SAND: light yellowish brown (2.5Y, 6/3), fine- to coarse-grained, medium-dense, wet.	SW			NA	6	30	
35								
40								
45								
50								
55								

Monterey #2/12 sand filter pack

2" Schedule 40 PVC slotted casing (0.02")

End cap



ATTACHMENT B - GROUNDWATER CONDITIONS



SYMBOLS

- B4 Previous soil boring
- Drum storage area
- 4.41 Groundwater monitoring well showing groundwater elevation in feet above msl
- MW1
- 4.3 Groundwater contour in feet above msl showing groundwater elevation
- Direction of groundwater flow

Groundwater is flowing S 50° E at a gradient of 0.005 feet/foot or 26 feet/mile.



TARGHEE, INC.
ENVIRONMENTAL CONSULTING

110 Pine Avenue, Suite 925
Long Beach, CA 90802
(562) 435-8080

GROUNDWATER CONDITIONS
JANUARY 14, 2002

DEL RAY CLEANERS
310 CULVER BOULEVARD
PLAYA DEL RAY, CALIFORNIA 90293

ATTACHMENT B

FEBRUARY 20, 2002

ATTACHMENT E

APPLICATION FOR WELL PERMIT

ENVIRONMENTAL HEALTH 2525 Corporate Place Monterey Park, Ca 91754

COUNTY OF LOS ANGELES DEPARTMENT OF HEALTH SERVICES

DATE

11-09-01

TYPE OF PERMIT (CHECK)

- ☒ NEW WELL CONSTRUCTION
☐ RECONSTRUCTION OR RENOVATION
☐ DESTRUCTION

TYPE OF WELL

- ☐ PRIVATE DOMESTIC
☐ PUBLIC DOMESTIC
☐ IRRIGATION
☒ OBSERVATION/MONITORING
☐ CATHODIC
☐ INDUSTRIAL
☐ GRAVEL PACK
☐ TEST

TYPE OF CASING

2" diameter schedule 40 PVC

METHOD OF SEALING OF CASING

Bentonite and Concrete


METHOD OF DESTRUCTION

ADDRESS (NUMBER, STREET, AND NEAREST INTERSECTION)

310 Culver Blvd ~~Playa Del Rey~~ @ Pershing Drive

CITY Playa Del Rey

DIAGRAM (SHOW PROPERTY LINES, STREET, ADDRESS, WELL SITE, SEWERS, AND PRIVATE SEWAGE DISPOSAL SYSTEMS ALONG WITH LABELS AND DIMENSIONS)



NAME OF WELL DRILLER (PRINT)

Gregg Drilling

TRADE NAME

NAME OF WELL OWNER (PRINT)

Del Rey Cleaners Barry Moeschel

MAILING ADDRESS

310 ~~Del Rey~~ Culver Blvd.

BUSINESS ADDRESS

2726 Walnut

CITY

Signal Hill

CITY

Playa Del Rey

I hereby agree to comply in every respect with all regulations of the County Preventive/Public Health Services and with all ordinances and laws of the County of Los Angeles and of the State of California pertaining to well construction, reconstruction and destruction. Upon completion of well and within ten days thereafter, I will furnish the County Preventive/Public Health Services with a complete log of the well, giving date drilled, depth of well, all perforations in casing, and any other data deemed necessary by such County Preventive/Public Health Services.

DISPOSITION OF APPLICATION: (For Sanitarians Use Only)

- ☒ APPROVED
☐ DENIED
☐ APPROVED WITH CONDITIONS

If denied or approved with conditions, report reason or conditions here:

DATE

12/10/01

SANITARIAN

SECTION CHIEF

Applicant's Signature 502 435 8080

Targhee
 110 Pine Ave #925
 Long Beach CA 90802

When signed by Section Chief, this application is a permit.

SERVICE APPLICATION AND FEE COLLECTION
COUNTY OF LOS ANGELES - DEPARTMENT OF HEALTH SERVICES
PUBLIC HEALTH PROGRAMS - ENVIRONMENTAL HEALTH
SERVICE REQUEST APPLICATION

INSTRUCTIONS

1. Check the TYPE OF SERVICE requested and attach the required non-refundable fee to the application. Make money order or check payable to LOS ANGELES COUNTY TREASURER, **DO NOT SEND CASH.** This application is nontransferable.

FEE REQUIRED*

TYPE OF SERVICE

- | | | |
|-----------------------------|--------------------------|---|
| <u> </u> | <input type="checkbox"/> | <u>MONITORING WELL CONSTRUCTION/DESTRUCTION</u> |
| <u> </u> | <input type="checkbox"/> | <u>WELL CONSTRUCTION, RENOVATION OR DESTRUCTION PERMIT</u>
Complete and attach a Well Permit Application |
| <u> </u> | <input type="checkbox"/> | <u>PRIVATE SEWAGE DISPOSAL SYSTEM CONSTRUCTION PERMIT</u> |
| <u> </u> | <input type="checkbox"/> | <u>PRIVATE SEWAGE DISPOSAL SYSTEM RENOVATION/EXPANSION</u> |
| <u> </u> | <input type="checkbox"/> | <u>INSPECTION OF MOUNTAIN CABIN SITE</u> as required by the
United States Forest Service |
| <u> </u> | <input type="checkbox"/> | <u>INSPECTION OF EXISTING PRIVATE SEWAGE SYSTEM</u> as required
by FHA/VA |
| <u> </u> | <input type="checkbox"/> | <u>WATER SUPPLY TEST AND CERTIFICATION</u> as required by U.S.
Department of Agriculture |

2. Check with Contact Office stamped below for requirements or information.
3. Complete the required information or deliver the completed application, money order or check with the forms indicated.

to: County of Los Angeles
Department of Health Services
Public Health Programs
Environmental Health
2525 Corporate Place
Monterey Park, Ca 91754
(213) 881-4147

* Refer to Schedule of Fees
for current fiscal year.

NOTE: FIELD PERSONNEL CANNOT ACCEPT FEES.

4. Phone Contact Office noted below, after you have received your receipt, to request an inspection.

Service/Job Location Address

Date

Owner/Applicant's Name

Address

Phone No.

Contractor's Name

Address

Phone No.

Co. Engineer Plan Check No. _____ Tract No. _____ Lot No. _____ No. Bedrooms _____
(Complete line above for Private Sewage Disposal System Construction or Renovation Application)

CONTACT OFFICE

DEPARTMENT STAMP

FEES PAID



Printed on recycled materials.

ATTACHMENT F

PSOMAS

February 5, 2002

Information and Engineering Solutions

Ms. Debbie Bechtold
Targhee, Inc.
110 Pine Avenue, Suite 925
Long Beach, CA 90802-4426

Subject: Monitor Well Locations at 310 Culver Boulevard, Los Angeles
Psomas Job No 1TAR0401

Dear Debbie:

Below are the locations for the three wells as surveyed by Psomas. I have also included a sketch of the wells. Please note that the names of the wells as marked in the field differed from the markup that Psomas had previously been provided.

Datums:

Horizontal: NAD83, California Coordinate System, Zone 5 (HPGN 1994.9)


Vertical: NGVD 1929, City of Los Angeles, 1985 Adjustment

Well Locations:

Well	Northing	Easting	Elev	
MW-1	1807993.21	6426022.29	8.40	Marked location on well
MW-2	1807959.62	6426090.58	16.99	Marked location on well
MW-3	1807954.40	6426006.82	11.64	Marked location on well

If I can be of any further assistance, please feel free to contact me.



Sincerely,

PSOMAS

John Chiappe Jr., PLS
Project Manager

JDC:jdc
attachment






Monitor Well Locations at 310 Culver Boulevard for Targee Inc

PSOMAS

DATE: 01/24/02 REVISED ON:
JOB No: 1TAR0401

NOTE: For reduced size prints, original scale is in inches.

ATTACHMENT G



AMERICAN SCIENTIFIC LABORATORIES, LLC

Environmental Testing Services

2520 N. San Fernando Rd., Los Angeles, CA 90065 Tel: (323) 223-9700 Fax: (323) 223-9500

RECEIVED

JAN 23 2002

Ordered By

Targhee, Inc.
110 Pine Ave. Ste. 925
Long Beach, CA 90802

Number of Pages 10

Date Received 01/09/2002

Date Reported 01/16/2002

Telephone (562) 435-8080
Attn Debra Bechtold

Job Number	Ordered	Client
12874	01/09/2002	TARGHE

Project ID: 310 CULVER
Project Name: Del Rey Cleaners
Site: 310 Culver
Playa Del Rey

Enclosed are the results of analyses on 6 samples analyzed as specified on attached chain of custody.

Wendy Lu
Organics Supervisor

Rojert G. Araghi
Laboratory Director

American Scientific Laboratories, LLC (ASL) accepts sample materials from clients for analysis with the assumption that all of the information provided to ASL verbally or in writing by our clients (and/or their agents), regarding samples being submitted to ASL, is complete and accurate. ASL accepts all samples subject to the following conditions:

- 1) ASL is not responsible for verifying any client-provided information regarding any samples submitted to the laboratory.
- 2) ASL is not responsible for any consequences resulting from any inaccuracies, omissions, or misrepresentations contained in client-provided information regarding samples submitted to the laboratory.



AMERICAN SCIENTIFIC LABORATORIES, LLC

2520 N. San Fernando Rd., Los Angeles, CA 90065 Tel: (323) 223-9700 Fax: (323) 223-9500

Page 1 of 1

ASL JOB# 12874

CHAIN OF CUSTODY RECORD									
Company: <u>Targhee</u>		Project Name: <u>Desrey Cleaners</u>		Report To: <u>D Buckwald</u>		ANALYSIS REQUESTED			
Address: <u>110 Pine Av #925</u>		Site Address: <u>310 Culver</u>		Address: <u>Targhee</u>					
Telephone: <u>562 435 8080</u>		Site Address: <u>Playa del Rey</u>		Invoice To: <u>Guatelle</u>					
Fax: <u>562 590 8793</u>		Project ID: <u>310 Culver</u>		Address: <u>Targhee</u>					
Special Instruction:		Project Manager: <u>D Buckwald</u>		P.O.#: <u>310 Culver</u>					
LAB USE ONLY		SAMPLE DESCRIPTION			CONTAINER(S)				
ITEM	Lab ID	Sample ID	Date	Time	#	Type	Matrix	Preservation	Remarks
1	79364	MW1-6.5	1-8-02		3	2 VOAS 1 brass	Soil	Sodium Bisulfate	Archive Brass
2	79365	MW2-6.5			2	2 VOAS			Archive Brass
3	79366	MW2-10.5			3	2 VOAS 1 Brass			
4	79367	MW3-6.5			3				
5	79368	MW3-10.5			3				
6	79369	MW3-15.5			3				
Collected By: <u>D Buckwald</u>		Date: <u>1-8-02</u>		Time: <u></u>		Relinquished By:		Date: <u>1/9/01</u>	
Relinquished By: <u>D Buckwald</u>		Date: <u>1-9-02</u>		Time: <u>2:50</u>		Received For Laboratory		Time: <u>2:50</u>	
Condition of Sample: <u>5 x Brass Soil Holder 12 x VOAS / No Brass Tube given for MW3 - 6.5</u>									