

## STREAM INVENTORY REPORT

### **Steelhead Creek**

#### INTRODUCTION

A stream inventory was conducted during the summer of 1996 on Steelhead Creek. The inventory was conducted in two parts: habitat inventory and biological inventory. The objective of the habitat inventory was to document the habitat available to anadromous salmonids in Steelhead Creek. The objective of the biological inventory was to document the presence and distribution of juvenile salmonid species. There is no known record of adult spawning surveys having been conducted on Steelhead Creek.

The objective of this report is to document the current habitat conditions, and recommend options for the potential enhancement of habitat for chinook salmon, coho salmon and steelhead trout. Recommendations for habitat improvement activities are based upon target habitat values suitable for salmonids in California's north coast streams.

#### WATERSHED OVERVIEW

Steelhead Creek is tributary to the Eel River, located in Humboldt County, California. Steelhead Creek's legal description at the confluence with the Eel River is T03S R05E S29. Its location is 40°10'18" North latitude and 123°41'00" West longitude. Steelhead Creek is a third order stream and has approximately 12.4 miles of blue line stream according to the USGS Fort Seward and Harris 7.5 minute quadrangles. Steelhead Creek drains a watershed of approximately 12.1 square miles. Summer base flow is approximately 0.5 cubic feet per second (cfs) at the mouth, but over 15 cfs is not unusual during winter storms. Elevations range from about 100 feet at the mouth of the creek to 3,000 feet in the headwater areas. Mixed conifer forest dominates the watershed. The watershed is entirely privately owned and is managed for rural residence. Vehicle access exists via Steelhead Road from the town of Alderpoint. Contact landowners for permission to enter and for more explicit directions to the mouth of Steelhead Creek.

#### METHODS

The habitat inventory conducted in Steelhead Creek follows the methodology presented in the *California Salmonid Stream Habitat*

*Restoration Manual* (Flosi and Reynolds, 1991 rev. 1994). The Pacific Coast Fisheries, Wetlands, and Wildlife restoration Association (PCFWWRA) members that conducted the inventory were trained in standardized habitat inventory methods by the California Department of Fish and Game (DFG). Steelhead Creek personnel were trained in May, 1996, by Scott Downie and Ruth Goodfield. This inventory was conducted by a two-person team.

### SAMPLING STRATEGY

The inventory uses a method that samples approximately 10% of the habitat units within the survey reach (Hopelain, 1994). All habitat units included in the survey are classified according to habitat type and their lengths are measured. All pool units are measured for maximum depth. Habitat unit types encountered for the first time are further measured for all the parameters and characteristics on the field form. Additionally, from the ten habitat units on each field form page, one is randomly selected for complete measurement.

### HABITAT INVENTORY COMPONENTS

A standardized habitat inventory form has been developed for use in California stream surveys and can be found in the *California Salmonid Stream Habitat Restoration Manual*. This form was used in Steelhead Creek to record measurements and observations. There are nine components to the inventory form.

#### 1. Flow:

Flow is measured in cubic feet per second (cfs) at the bottom of the stream survey reach using standard flow measuring equipment, if available. In some cases flows are estimated.

#### 2. Channel Type:

Channel typing is conducted according to the classification system developed and revised by David Rosgen (1985 rev. 1994). This methodology is described in the *California Salmonid Stream Habitat Restoration Manual*. Channel typing is conducted simultaneously with habitat typing and follows a standard form to record measurements and observations. There are five measured parameters used to determine channel type: 1) water slope gradient, 2) entrenchment, 3) width/depth ratio, 4) substrate composition, and 5) sinuosity.

#### 3. Temperatures:

Both water and air temperatures are measured and recorded at every tenth habitat unit. The time of the measurement is also recorded. Both temperatures are taken in degrees Fahrenheit at the middle of the habitat unit and within one foot of the water surface. Additionally, a recording thermograph was deployed in Steelhead Creek from 6/26/96 to 10/17/96 to record temperatures on a 24 hour basis during warm summer months.

#### 4. Habitat Type:

Habitat typing uses the 24 habitat classification types defined by McCain and others (1988). Habitat units are numbered sequentially and assigned a type identification number selected from a standard list of 24 habitat types. Dewatered units are labeled "dry". Steelhead Creek habitat typing used standard basin level measurement criteria. These parameters require that the minimum length of a described habitat unit must be equal to or greater than the stream's mean wetted width. Channel dimensions were measured using hip chains, range finders, tape measures, and stadia rods. All units were measured for mean length; additionally, the first occurrence of each unit type and a randomly selected 10% subset of all units were sampled for all features on the sampling form (Hopelain, 1995). Pool tail crest depth at each pool unit was measured in the thalweg. All measurements were in feet to the nearest tenth.

#### 5. Embeddedness:

The depth of embeddedness of the cobbles in pool tail-out reaches is measured by the percent of the cobble that is surrounded or buried by fine sediment. In Steelhead Creek, embeddedness was ocularly estimated. The values were recorded using the following ranges: 0 - 25% (value 1), 26 - 50% (value 2), 51 - 75% (value 3), 76 - 100% (value 4). Additionally, a rating of "not suitable" (NS) was assigned to tail-outs deemed unsuited for spawning due to inappropriate substrate particle size, having a bedrock tail-out, or other considerations.

#### 6. Shelter Rating:

Instream shelter is composed of those elements within a stream channel that provide salmonids protection from predation, reduce water velocities so fish can rest and conserve energy, and allow separation of territorial units to reduce density related competition. The shelter rating is calculated for each fully-described habitat unit by multiplying shelter value and percent cover. Using an overhead view, a quantitative estimate of the percentage of the habitat unit covered is made. All cover is then classified according to a list of nine cover types. In Steelhead Creek, a standard qualitative shelter value of 0

(none), 1 (low), 2 (medium), or 3 (high) was assigned according to the complexity of the cover. Thus, shelter ratings can range from 0-300 and are expressed as mean values by habitat types within a stream.

#### 7. Substrate Composition:

Substrate composition ranges from silt/clay sized particles to boulders and bedrock elements. In all fully-described habitat units, dominant and sub-dominant substrate elements were ocularly estimated using a list of seven size classes and recorded as a one and two respectively.

#### 8. Canopy:

Stream canopy density was estimated using modified handheld spherical densimeters as described in the *California Salmonid Stream Habitat Restoration Manual*, 1994. Canopy density relates to the amount of stream shaded from the sun. In Steelhead Creek, an estimate of the percentage of the habitat unit covered by canopy was made from the center of approximately every third unit in addition to every fully-described unit, giving an approximate 30% sub-sample. In addition, the area of canopy was estimated ocularly into percentages of coniferous or deciduous trees.

#### 9. Bank Composition and Vegetation:

Bank composition elements range from bedrock to bare soil. However, the stream banks are usually covered with grass, brush, or trees. These factors influence the ability of stream banks to withstand winter flows. In Steelhead Creek, the dominant composition type (options 1-4) and the dominant vegetation type (options 5-9) of both the right and left banks for each fully-described unit were selected from the habitat inventory form. Additionally, the percent of each bank covered by vegetation was estimated and recorded.

### BIOLOGICAL INVENTORY

Biological sampling during stream inventory is used to determine fish species and their distribution in the stream. In Steelhead Creek fish presence was observed from the stream banks. This sampling technique is discussed in the *California Salmonid Stream Habitat Restoration Manual*.

### SUBSTRATE SAMPLING

Gravel sampling is conducted using a 9 inch diameter standard McNeil gravel sampler. Sample sites are identified numerically beginning at the most upstream site in the stream. Gravel samples are separated and measured to determine respective percent volume using five sieve sizes (25.4, 12.5, 4.7, 2.37, and 0.85 mm) (Valentine, 1995).

#### DATA ANALYSIS

Data from the habitat inventory form are entered into *Habitat*, a dBASE 4.2 data entry program developed by Tim Curtis, Inland Fisheries Division, California Department of Fish and Game. This program processes and summarizes the data, and produces the following six tables:

- Riffle, flatwater, and pool habitat types
- Habitat types and measured parameters
- Pool types
- Maximum pool depths by habitat types
- Dominant substrates by habitat types
- Mean percent shelter by habitat types

Graphics are produced from the tables using Lotus 1,2,3.

Graphics developed for Steelhead Creek include:

- Riffle, flatwater, pool habitats by percent occurrence
- Riffle, flatwater, pool habitats by total length
- Total habitat types by percent occurrence
- Pool types by percent occurrence
- Total pools by maximum depths
- Embeddedness
- Pool cover by cover type
- Dominant substrate in low gradient riffles
- Percent canopy
- Bank composition by composition type
- Bank vegetation by vegetation type

#### HABITAT INVENTORY RESULTS

\* ALL TABLES AND GRAPHS ARE LOCATED AT THE END OF THE REPORT \*

The habitat inventory of October 17 to 23, 1996, was conducted by Frank Humphrey and Dave Smith (PCFWWRA). The total length of the stream surveyed was 14,776 feet with an additional 47 feet of side channel.

Flow was estimated to be 1.0 cfs during the survey period.

Steelhead Creek is an F2 channel type for the first 9,018 feet

of stream reach surveyed, and a B4 for the remaining 5,758 feet of stream surveyed. F2 channels are entrenched, meandering, riffle/pool channels on low gradients with high width/depth ratios and boulder dominant substrates. B4 channel types are moderately entrenched, moderate gradient, riffle-dominated channel with stable banks and gravel-dominant substrates.

Water temperatures taken during the survey period ranged from 50 to 57° Fahrenheit. Air temperatures ranged from 52 to 67° F. Water temperatures taken with a recording thermograph deployed from June 26 to October 17, 1996, ranged from 53° to 77° F.

Table 1 summarizes the Level II riffle, flatwater, and pool habitat types. Based on frequency of **occurrence** there were 46% riffle units, 30% flatwater units, and 23% pool units (Graph 1). Based on total **length** of Level II habitat types there were 49% riffle units, 35% flatwater units, and 14% pool units (Graph 2).

Eleven Level IV habitat types were identified (Table 2). The most frequent habitat types by percent **occurrence** were step runs, 24%; high gradient riffles, 24%; and low gradient riffles, 15% (Graph 3). Based on percent total **length**, step runs made up 31%, low gradient riffles 21%, and high gradient riffles 21%.

A total of sixty-nine pools were identified (Table 3). Main channel pools were most frequently encountered at 78% and comprised 87% of the total length of all pools (Graph 4).

Table 4 is a summary of maximum pool depths by pool habitat types. Pool quality for salmonids increases with depth. fifty-five of the 69 pools (80%) had a depth of two feet or greater (Graph 5).

The depth of cobble embeddedness was estimated at pool tail-outs. Of the 69 pool tail-outs measured, none had a value of 1 (0%); 20 had a value of 2 (29%); 28 had a value of 3 (49%); and one had a value of 4 (1%) (Graph 6). On this scale, a value of 1 indicates the highest quality of spawning substrate.

A shelter rating was calculated for each habitat unit and expressed as a mean value for each habitat type within the survey using a scale of 0-300. Pool habitat types had a mean shelter rating of 30, and riffle habitats had a mean shelter rating of 26 (Table 1). Of the pool types, the scour pools had the highest mean shelter rating at 48. Main channel pools had a mean shelter rating of 25 (Table 3).

Table 5 summarizes mean percent cover by habitat type. Boulders

re the dominant cover type in Steelhead Creek and are extensive. Large and small woody debris are lacking in nearly all habitat types. Graph 7 describes the pool cover in Steelhead Creek.

Table 6 summarizes the dominant substrate by habitat type. Gravel was the dominant substrate observed in five of the eight low gradient riffles measured (63%). Boulder was the next most frequently observed dominant substrate type and occurred in 25% of the low gradient riffles (Graph 8).

The mean percent canopy density for the stream reach surveyed was 31%. The mean percentages of deciduous and coniferous trees were 89% and 11%, respectively (Graph 9).

For the stream reach surveyed, the mean percent right bank vegetated was 64%. The mean percent left bank vegetated was 50%. The dominant elements composing the structure of the stream banks consisted of 3.6% bedrock, 55.4% boulder, 33.9% cobble/gravel, and 7.1% sand/silt/clay (Graph 10). Brush was the dominant vegetation type observed in 18% of the units surveyed. Additionally, 63.4% of the units surveyed had deciduous trees as the dominant vegetation type, and 2.7% had coniferous trees as the dominant vegetation, including down trees, logs, and root wads (Graph 11).

#### BIOLOGICAL INVENTORY RESULTS

Young-of-the-year (YOY) and juvenile (1+) steelhead rainbow trout were observed from the streambanks by Frank Humphrey and Greg Mullins (PCFWWRA) during the 1996 summer stream survey.

#### GRAVEL SAMPLING RESULTS

No gravel samples were taken on Steelhead Creek.

#### DISCUSSION

Steelhead Creek is an F2 channel type for the first 9,018 feet of stream surveyed and a B4 for the remaining 5,758 feet. The suitability of F2 channel types for fish habitat improvement structures is fair for low-stage weirs, single and opposing wing-deflectors, and log cover; and poor for medium-stage weirs. The suitability of B4 channel types for fish habitat improvement structures is excellent for low-stage plunge weirs, boulder clusters and bank-placed boulders; and good for medium-stage plunge weirs.

The water temperatures recorded on the survey days October 17 to 23, 1996, ranged from 50 to 57 degrees Fahrenheit. Air temperatures ranged from 52 to 67 degrees Fahrenheit. Further samples from a recording thermograph deployed during the summer of **1996** measured water temperatures that ranged from 53° to 77° Fahrenheit. This is a relatively warm water temperature range for salmonids. Temperatures above 68° F, if sustained, are near the threshold stress level for salmonids. This seems to be the case here, and Steelhead Creek seems to have temperatures above optimum levels for salmonids.

Flatwater habitat types comprised 35% of the total **length** of this survey, riffles 49%, and pools 14%. The pools are relatively shallow, with only 28 of the 69 (41%) pools having a maximum depth greater than 3 feet. In general, pool enhancement projects are considered when primary pools comprise less than 40% of the length of total stream habitat. In third and fourth order streams, a primary pool is defined to have a maximum depth of at least three feet, occupy at least half the width of the low flow channel, and be as long as the low flow channel width. Installing structures that will increase or deepen pool habitat is recommended for locations where their installation will not be threatened by high stream energy, or where their installation will not conflict with the modification of the numerous log debris accumulations (LDA's) in the stream.

Twenty-nine of the 69 pool tail-outs measured had embeddedness ratings of 3 or 4. None had a 1 rating. Cobble embeddedness measured to be 25% or less, a rating of 1, is considered to indicate good quality spawning substrate for salmon and steelhead. In Steelhead Creek, sediment sources should be mapped and rated according to their potential sediment yields, and control measures should be taken.

The mean shelter rating for pools was low with a rating of 33. The shelter rating in the flatwater habitats was slightly lower at 18. A pool shelter rating of approximately 100 is desirable. The relatively small amount of cover that now exists is being provided primarily by boulders in all habitat types. Additionally, whitewater contributes a small amount. Log and root wad cover structures in the pool and flatwater habitats are needed to improve both summer and winter salmonid habitat. Log cover structure provides rearing fry with protection from predation, rest from water velocity, and also divides territorial units to reduce density related competition.

Six of the eight low gradient riffles measured had gravel or small cobble as the dominant substrate. This is generally considered good for spawning salmonids.



The mean percent canopy density for the stream was 31%. This is a relatively low percentage of canopy. In general, re-vegetation projects are considered when canopy density is less than 80%.

The percentage of right and left bank covered with vegetation was moderate at 64% and 50%, respectively. In areas of stream bank erosion or where bank vegetation is not at acceptable levels, planting endemic species of coniferous and deciduous trees, in conjunction with bank stabilization, is recommended.

### RECOMMENDATIONS

- 1) Steelhead Creek should be managed as an anadromous, natural production stream.
- 2) Where feasible, design and engineer pool enhancement structures to increase the number of pools. This must be done where the banks are stable or in conjunction with stream bank armor to prevent erosion.
- 3) Increase woody cover in the pools and flatwater habitat units. Most of the existing cover is from boulders. Adding high quality complexity with woody cover is desirable and in some areas the material is locally available.
- 4) The limited water temperature data available suggest that maximum temperatures are above the optimum range for juvenile salmonids. To establish more complete and meaningful temperature regime information, 24-hour monitoring during the July and August temperature extreme period should be performed for 3 to 5 years.
- 5) Increase the canopy on Steelhead Creek by planting willow, alder, and Douglas fir along the stream where shade canopy is not at acceptable levels. The reaches above this survey section should be inventoried and treated as well, since the water flowing here is effected from upstream. In many cases, planting will need to be coordinated to follow bank stabilization or upslope erosion control projects.

### PROBLEM SITES AND LANDMARKS

The following landmarks and possible problem sites were noted. All distances are approximate and taken from the beginning of the survey reach.

0' Begin survey at confluence with the Eel River.  
Channel type is an F2 for the first 9018' of stream surveyed.

1927' Powers Creek enters stream from right bank (RB).  
Temperature of Powers Creek is 51°F.

1970' Spring on RB.

2076' Bank failure on left bank (LB) - looks fresh.

3141' Spring on RB.

3349' Adult steelhead carcass found on a boulder by the surveyors.

3425' Failure on LB; approximately 250' long x 60' high.

4326' Young-of-the-year (YOY) salmonids observed from the streambanks.

4359' Tributary enters from LB - 48°F.

4446' Failure on RB; approximately 60' long x 15' high.  
Contributing fines directly to the stream channel.

5264' Old failure on RB; 40' long x 15' high. Still contributing fines to stream.

5376' Dry tributary on LB.

5555' Dry tributary on LB.

5604' YOY salmonids observed from streambanks.

5798' Dry tributary on LB.

6219' Large debris accumulation (LDA) in stream channel; approximately 20' long x 10' wide x 5' high. Does not appear to be a barrier for migrating fish.

6361' YOY salmonids observed from streambanks.

6685' Tributary on LB; temperature is 51°F.

7085' Multiple springs on the RB; 56°F. Surveyors noted that approximately half of the total stream flow at that point was coming from these springs.

7527' LDA in stream channel; 10' long x 15' wide x 5' high.  
Not a barrier to fish.

7994' Dry tributary on the LB.

8770' Lateral erosion occurring on RB; approximately 40'  
long x 15' high. Contributing fines to stream.

9019' Channel type changes to a B4 for the remaining 5758'  
of stream surveyed.

9358' LDA in stream channel; 20' long x 10' wide x 5' high.  
Not a barrier to fish.

11176' Tributary on RB - 50°F.

11908' Numerous YOY steelhead rainbow trout observed from the  
streambanks.

12363' Large tributary enters from LB - 54°F. Surveyors  
estimate that approximately half of the stream flow at  
this point comes from the tributary.

12447' Spring on LB.

12558' Spring on RB.

12911' LDA in stream channel; 10' long x 40' wide x 10' high.  
Vertical drop in water elevation of 5-feet. Possible  
barrier to fish.

14069' LDA in stream; 25' long x 20' wide x 5' high. Possible  
barrier to fish.

14213' Two YOY steelhead rainbow trout observed from the  
streambanks.

14552' Failure on LB; 100' long x 15' high.

14725' LDA in stream channel; 15' long x 30' wide x 10' high.  
The LDA is retaining gravel and seems to be  
exacerbating failure on LB.

14776' Stream gradient is steepening dramatically. There are  
multiple waterfalls within the next several hundred  
feet of stream. End of anadromy. End of survey.

## References

- Flosi, G., and F. Reynolds. 1994. California salmonid stream habitat restoration manual, 2nd edition. California Department of Fish and Game, Sacramento, California.
- Hopelain, J. 1995. Sampling levels for fish habitat inventory, unpublished manuscript. California Department of Fish and Game, Inland Fisheries Division, Sacramento, California.
- Valentine, B. 1995. Stream substrate quality for salmonids: guidelines for sampling, processing, and analysis, unpublished manuscript. California Department of Forestry and Fire Protection, Santa Rosa, California.

LEVEL III and LEVEL IV HABITAT TYPE KEY

HABITAT TYPE	LETTER	NUMBER
<b>RIFFLE</b>		
Low Gradient Riffle	[LGR]	1.1
High Gradient Riffle	[HGR]	1.2
<b>CASCADE</b>		
Cascade	[CAS]	2.1
Bedrock Sheet	[BRS]	2.2
<b>FLATWATER</b>		
Pocket Water	[POW]	3.1
Glide	[GLD]	3.2
Run	[RUN]	3.3
Step Run	[SRN]	3.4
Edgewater	[EDW]	3.5
<b>MAIN CHANNEL POOLS</b>		
Trench Pool	[TRP]	4.1
Mid-Channel Pool	[MCP]	4.2
Channel Confluence Pool	[CCP]	4.3
Step Pool	[STP]	4.4
<b>SCOUR POOLS</b>		
Corner Pool	[CRP]	5.1
Lateral Scour Pool - Log Enhanced	[LSL]	5.2
Lateral Scour Pool - Root Wad Enhanced	[LSR]	5.3
Lateral Scour Pool - Bedrock Formed	[LSBk]	5.4
Lateral Scour Pool - Boulder Formed	[LSBo]	5.5
Plunge Pool	[PLP]	5.6
<b>BACKWATER POOLS</b>		
Secondary Channel Pool	[SCP]	6.1
Backwater Pool - Boulder Formed	[BPB]	6.2
Backwater Pool - Root Wad Formed	[BPR]	6.3
Backwater Pool - Log Formed	[BPL]	6.4
Dammed Pool	[DPL]	6.5