

Response Strategy Site: Rio Bravo Boat Launch (KER-215)

Site Description and Field Notes					
River Width:	Site Location/Segment: KER-KN-G-015				
50 meters (164 feet)	Located on Rio Bravo Ranch, Nickel Family, LLC property. There is a gate to access the river that might be locked				
Gradient: Low	Limited room to stage vehicles and equipment. A larger staging area is available at the Rio Bravo Ranch, Nickel Family, LLC headquarters located at 15701 Highway 178 Bakersfield, CA 93306.				
Site Contact/s:	Vehicular Access: Passenger vehicles, small trucks, small trailers, small vacuum truck				
Jeff Siemens, Rio Bravo Ranch, Nickel Family, LLC	Recreational Use: Rafting, Human Contact				
Mobile: (661) 364-3010	Boat Launches: Direct river access, shallow boat launch for small skiff (river left). Private residence with river access/boat launch on river right.				
City of Bakersfield Water Resources (661) 326-3716	ESI Shoreline Type: 1A Exposed rocky bank/shore; 8F Vegetated, steeply-sloping bluffs; 9B Vegetated low banks				

Site Images



Upstream



Downstream



Straight Across

RR = River Right RL = River Left

Photo Date: 02/07/2018

Page 2 of 3

Response Strategy Site: Rio Bravo Boat Launch (KER-215)

Site Objectives: Boom to prevent further movement of oil and allow for collection of oil.

Implementation: Deploy 400 ft. of containment boom upstream at an angle to prevent entrainment, utilizing trees as existing anchor points or using anchoring stakes. Oil collection will be on river left.

Staging Area Location and Capabilities/Amenities/Waste Management: Limited staging on river left. Boom trucks, trailer, vacuum trucks and temporary storage tanks could use the space, but it is limited. Access on river right limited due to private residence. Could access river right with a small skiff. Large staging location at Rio Bravo Ranch, Nickel Family, LLC headquarters. No restrooms or electricity onsite.

Response Strategy Map (overview)



Table of Response Resources							
Туре	Sub-Type	Size	Unit	QTY - Unit	Special Equipment or Comments		
Boom	Swamp	12	Inch	400 ft.	Booming strategy only effective during medium to low flow		
Boom	Sorbent	5 or 8	Inch	400 ft.	5 inches for light oiling, 8 inches for heavier oiling		
Skimmer	Drum				Number will vary depending on response.		
Stakes	Anchoring			6	6 stakes per boom, 3 on either end. Any boom with a "J" in it shape would require an additional stake. Recommend angle iron beams.		
Anchors	Danforth	40	lb	1	Midstream anchoring.		
Boat	Small Skiff			1	Only necessary if river currents and water levels are optimal for launching a skiff to deploy boom.		
Personnel				8	4 boat crew and 4 shoreside personnel.		