

Response Strategy S	Site: Round Mountain Road (KER-270) Page 2 of 3					
Site Description and Field Notes						
River Width: 50 meters (164 feet)	Site Location/Segment: KER-KN-H-010					
Gradient: Low	This location has multiple dirt access roads that reach the river's edge (river right). The roads are narrow, dirt roads with trash often dumped in the vicinity. Vehicles are often parked along the edge of the river and public use is heavy					
Site Contact/s: City of Bakersfield Water Resources (661) 326-3716 Larry Swan, Kern County Parks and Recreation (661) 868 - 7010	at times. Recreational gold panning occurs at this location occasionally. Access to river left is at Hart Park off River Road.					
	Vehicular Access: Passenger vehicles, small trucks, vacuum trucks, trailers					
	Recreational Use: Tubing, human contact, gold panning, recreational fishing					
	Boat Launches: Direct river access, shallow boat launch (river right) for small skiff					
After hours contact Sheriff dispatch at (661) 861 - 3110	ESI Shoreline Type: 8F vegetated, steeply-sloping bluffs; 9B vegetated low banks					

Site Images





Upstream

Downstream





RR = River Right RL = River Left

Photo Date: 11/15/2017

Response Strategy Site: Round Mountain Road (KER-270)

Page 3 of 3

Site Objectives: Boom to prevent further movement of oil and allow for collection of oil

Implementation: Deploy 300 ft. of containment boom upstream at an angle to prevent entrainment, utilizing trees as existing anchor points or using anchoring stakes. Oil collection will be on river right.

Staging Area Location and Capabilities/Amenities/Waste Management: Staging on river right. Boom trucks, trailer, vacuum trucks and temporary storage tanks could use the space – would need county's permission. Room for decontamination. No electricity or bathrooms present.

Response Strategy Map (overview)



Table of Response Resources						
Туре	Sub-Type	Size	Unit	QTY - Unit	Special Equipment or Comments	
Boom	Swamp	12		300 ft.	Booming strategy only effective during medium to low flow	
Boom	Sorbent	5 or 8		300 ft.	5 inches for light oiling, 8 inches for heavier oiling	
Stakes	Anchoring			6	6 stakes per boom, 3 on either end. Any boom with a "J" in it shape would require an additional stake. Recommend angle iron beams.	
Anchors	Danforth	40	lb	1	Midstream anchoring.	
Skimmer	Drum				Number will vary depending on response.	
Boat	Small Skiff			1	Only necessary if river currents and water levels are optimal for launching a skiff to deploy boom.	
Personnel				8	4 boat crew and 4 shoreside personnel.	